



# MSDS

## MATERIAL SAFETY DATA SHEET *Butyl Flashing Grade 321*

### SECTION 1: PRODUCT IDENTIFICATION

Manufacturer's Name: American WeatherStar  
Address: PO Box 6256  
Mobile AL 36660

Emergency Telephone: INFOTRAC— 800/535-5053

PRODUCT NAME: Butyl Flashing Grade 321

### SECTION 2A: HAZARDOUS INGREDIENTS

INGREDIENT	CAS #	PERCENT	OCCUPATIONAL EXPOSURE LIMIT		VAPOR PRESSURE
			TLV	PEL	

This product contains no hazardous ingredients as defined in 29 CFR Section 1910.1200 (g)(1)(2).

### SECTION 2B: ADDITIONAL INGREDIENTS (>3%)

INGREDIENT	CAS #	INGREDIENT	CAS #
Polybutene	9003-29-6	Hydrocarbon Resin	25038-32-8
Hydrocarbon Resin	62258-49-5	Calcium Carbonate	1317-65-3
Hydrocarbon Resin	9003-07-0	Butyl Rubber	9010-85-9

### SECTION 3: PHYSICAL DATA

N/A=NOT APPLICABLE N/E=NOT ESTABLISHED

BOILING RANGE: 314°F (157°C)	VAPOR DENSITY: N/A
EVAPORATION RATE: N/A	% VOLATILE WEIGHT: None
PHYSICAL STATE: Gray tacky tape	VAPOR MEASURE: N/A
SPECIFIC GRAVITY: 1.25	SOLUBILITY IN WATER: Not soluble
CORROSIVITY: N/A	ODOR THRESHOLD: N/A
FREEZING POINT: N/E	pH: N/A

ODOR & APPEARANCE: Gray tacky tape with mild rubber odor (1602 polyester backed)



# MSDS

## MATERIAL SAFETY DATA SHEET

### *Butyl Flashing Grade 321*

#### SECTION 4: FIRE AND EXPLOSION HAZARD DATA

---

FLAMMABILITY CLASSIFICATION: NOT FLAMMABLE

FLASH POINT: None-TCC

LOWER FLAMMABLE LIMIT: N/A

UPPER FLAMMABLE LIMIT: N/A

AUTOIGNITION TEMPERATURE: N/A

HAZARDOUS COMBUSTION PRODUCTS: Carbon Monoxide & Carbon Dioxide

EXTINGUISHING MEDIA: Water, Dry Chemical, Foam, and Carbon Dioxide

UNUSUAL FIRE AND EXPLOSION HAZARDS: There is no evidence that this product is sensitive physical shock or static discharge

SPECIAL FIREFIGHTING PROCEDURES: Follow normal fire fighting procedures.

Firefighters should wear self-contained breathing apparatus, especially in enclosed areas.

Will not burn unless preheated.

#### SECTION 5: HEALTH HAZARD DATA

---

EFFECTS OF OVEREXPOSURE:

No known effects. Considered nontoxic and noninjurious.

Eye contact may cause mechanical irritation.

Skin contact may cause mechanical irritation.

Ingestion or inhalation highly unlikely. Low order of acute oral toxicity.

All evidence indicates that large polymer molecules are not biologically inactive.

#### SECTION 6: REACTIVITY DATA

---

STABILITY: STABLE

HAZARDOUS POLYMERIZATION: Will not occur.

HAZARDOUS DECOMPOSITION PRODUCTS: Combustion may yield a variety of compounds such as, CO, CO<sub>2</sub>, simple hydrocarbons, acids, aldehydes, ketones.

CONDITIONS TO AVOID: Keep away from excessive heat.

INCOMPATIBILITY (MATERIALS TO AVOID): Avoid strong acids and strong oxidizing agents.



# MSDS

## MATERIAL SAFETY DATA SHEET

### *Butyl Flashing Grade 321*

#### SECTION 7: PREVENTIVE MEASURES

---

EYE PROTECTION: Glasses or Goggles

GLOVES: Cotton or other protective gloves

LEAK or SPILL PROCEDURES: N/A

RESPIRATOR: Not needed

WASTE DISPOSAL: Dispose of in accordance with all state, local, and federal regulations.

OTHER: Long sleeves & long trousers to prevent skin contact. Industrial Shoes to prevent contact.

HANDLING PROCEDURES AND EQUIPMENT: Keep out of reach of children.

Wash with soap and water after use, especially before eating, smoking, or drinking

STORAGE REQUIREMENTS: Keep away from excessive heat. Material may flow and could create a duration contact burn on hand.

SPECIAL SHIPPING INFORMATION: Item 35240 Class 55

#### SECTION 8: FIRST AID MEASURES

---

EYE CONTACT: Do not remove. Get medical attention.

SKIN CONTACT: Care should be taken in the removal of the hot melt adhesive.

Get medical attention if too sensitive.

INHALATION: N/A

INGESTION: Unlikely, but if ingested, it could create a blockage. Get medical attention.

#### SECTION 9: SARA SECTION 313 SUPPLIER NOTIFICATION

---

This product contains the following toxic chemicals subject to the reporting requirements of Section 313 of the Emergency Planning & Community Right-to-Know Act of 1986 of 49 CFR 372.

Chemical Name \_\_\_\_\_ CAS # \_\_\_\_\_ %