



MSDS

MATERIAL SAFETY DATA SHEET

Fast Set Urethane 530 Part A

SECTION 1: PRODUCT IDENTIFICATION

Manufacturer's Name: American WeatherStar
Address: PO Box 6256
Mobile AL 36660

Emergency Telephone: INFOTRAC— 800/535-5053

PRODUCT NAME: Fast Set Urethane 530 Part A

Hazard Ratings:	Health	1	1= Slight
	Flammability	0	0= Least
	Reactivity	0	0= Least
	Personal Protection	B	

SECTION 2: HAZARDOUS SUBSTANCES

% BY WT	TLV
None currently known	

SECTION 3: PHYSICAL DATA

BOILING RANGE: Over 300 Deg. F

WEIGHT PER GALLON: 8.6 Lbs

VAPOR DENSITY: Not Available

VOC: 0 grams/liter

% VOLATILE BY VOLUME: Non-Volatile

EVAPORATION RATE: N/A



MSDS

MATERIAL SAFETY DATA SHEET

Fast Set Urethane 530 Part A

SECTION 4: FIRE & EXPLOSION HAZARD DATA

Non-flammable Liquid.

EXTINGUISHING MEDIA: Foam, CO₂, dry chemical or water fog.

SPECIAL FIRE FIGHTING PROCEDURES: Firefighters must wear self-contained breathing apparatus to protect against toxic and/or irritating fumes.

UNUSUAL FIRE & EXPLOSION HAZARD: Carbon monoxide may be evolved if combustion incomplete. This product is non-flammable and will not explode due to mechanical impact.

SECTION 5: HEALTH HAZARD DATA

EFFECTS OF OVEREXPOSURE: Skin or eye contact cause irritation, redness and/or burning.

EMERGENCY & FIRST AID: Eye contact: flush with water for at least 15 minutes and call a physician as soon as possible. Skin contact; wash with soap and water and remove contaminated clothing. Ingestion; see a physician immediately.

PRIMARY ROUTES OF ENTRY: Dermal most likely.

MEDICAL CONDITIONS PRONE TO AGGRAVATION BY EXPOSURE: Repeated and long term skin contact may result in sensitization.

SECTION 6: REACTIVITY DATA

STABILITY: Stable

CONDITIONS TO AVOID: Temperature extremes.

INCOMPATIBILITY: Avoid contact with strong oxidizing materials like liquid chlorine and concentrated oxygen.

HAZARDOUS DECOMPOSITION PRODUCTS: Carbon monoxide and/or carbon dioxide may be produced if combustion incomplete.

HAZARDOUS POLYMERIZATION: Will not occur.



MSDS

MATERIAL SAFETY DATA SHEET *Fast Set Urethane 530 Part A*

SECTION 7: SPILL OR LEAK PROCEDURES

STEPS TO BE TAKEN IN CASE MATERIAL IS RELEASED OR SPILLED: Recover free liquid. Cover remaining spill with sawdust, vermiculite, or other absorbent material to minimize spreading before collecting for disposal.

WASTE DISPOSAL METHOD: Dispose in accordance with local, state, and federal regulations.

SECTION 8: SPECIAL PROTECTION INFORMATION

RESPIRATORY PROTECTION: Contains isocyanates when mixed with U-8730 Part B. Use self-contained or supplied air breathing apparatus in areas where the isocyanate concentration is above the PEL or when the material is being heated or spray applied. (See Part B MSDS)

VENTILATION (Local Exhaust): Good general room ventilation. Mechanical ventilation in enclosed areas.

PROTECTIVE GLOVES: Chemical resistant gloves. Nitrile recommended

EYE PROTECTION: Safety goggles or face shield.

OTHER PROTECTIVE EQUIPMENT: Eye bath & safety shower should be available.

SECTION 9: SPECIAL PRECAUTIONS & TOXICOLOGICAL PROPERTIES

SPECIAL PRECAUTIONS TO BE TAKEN IN HANDLING & STORING: Keep containers closed and store in a cool dry place away from direct sunlight.

TOXICOLOGICAL PROPERTIES: Available data shows that none of the ingredients are carcinogenic, teratogenic or mutagenic. However, swallowing this material may be harmful or fatal.

This information is furnished without warranty, representation, inducement, or license of any kind, expressed or implied, including any implied warranty of merchantability or of fitness for a particular purpose, except that it is accurate to the best of Gaco Western's knowledge or obtained from sources believed to be accurate. Gaco Western Inc. does not assume any legal responsibility for use or reliance upon same. It is the user's obligation to determine the conditions of safe use of this product.